SENTER®

SD917D

4 inch Android 13 PDA



Functions

4.0-inch HD screen • High speed Quad - Core Android 13.0 system • 4G full Netcom

Android | 4G | WIFI | Bluetooth | 1D scanning | 2D scanning | PSAM | NFC | Camera | GPS



Product parameters

SD917D

Performance

CPU	Cortex-A53 Quad core 64 bit 2.0 GHz high performance processor
RAM+ROM	2GB+16GB
Expand memory	Micro SD(TF) Supports up to 128GB
System	Android 13.0

Data communication

WLAN	Dual-band 2.4GHz / 5GHz, Supporting IEEE 802 a/b/g/n/ac protocol
WWAN	2G：GSM（850/900/1800/1900MHz）
	3G：WCDMA（850/900/1900/2100MHz）
	4G： FDD:B1/B3/B4/B7/B8/B12/B20 TDD:B38/B39/B40/B41
Bluetooth	Support Bluetooth 2.1+EDR/3.0+HS/4.1+HS Transmission distance 5-10 meters

Physical parameter

Dimension	162mm×71.5mm×17（The thinnest part）mm
Weight	＜300g
Display	4.0 inch TN color display with resolution 480*800
TP	Support multi-touch
Battery capacity	Rechargeable polymer battery (3.8V 4500mah) removable
	Standby time >350 hours
	Working time > 12 hours
	Charging time ＜5H, using standard power adapter and data cable
Expansion Card slot	Nano SIM card x 2, TF card x 1
Communication interface	Type-C 2.0 USB x 1, supporting OTG function
	POGO Pin x 1
Audio	Speaker (mono), Microphone, Earpiece
Keypad	25 soft and hard rubber buttons, left button x1, right button x1
Sensor	Gravity sensor, light sensor, distance sensor, vibration motor

Data collection

Barcode scanning (Optional)

1D Linear scanner	Mindeo SE966 Honeywell N4313
1D Symbologies	Code128,EAN-13,EAN-8,Code39,UPC-A,UPC-E,Co daber,Interleaved 2 of 5,China post 25,ISBN/ISSN,Code93, UCC/EAN-128,GS1Databar,HIBC,
2D Imager scanner	Mindeo E483/ EM6601, Honeywell N6603/ N3603
2D Symbologies	PDF417,Micro PDF417,GS1 Composite,Aztec Code,Data Matrix,QR Code,Micro QR Code,MaxiCode,Hanxin Code,

Camera（standard）

Rear camera	800W pixel HD camera Support auto focus, Flash, Anti-shake, Macro shooting
Front camera	500W pixel color camera

NFC (Optional)

Frequency	13.56MHz
Protocol	Support ISO14443A/B, 15693 agreement
Distance	2cm-5cm

Language/ Input method

Input	English, Pinyin, Five strokes, Handwriting input, Support soft keypad
Language	Language packs in Simplified Chinese, Traditional Chinese，English, Korean, Japanese, Malaysian, etc.

User environment

Operating Temperature	-20℃ - 55℃
Storage Temperature	-40℃ - 70℃
Environment Humidity	5%RH--95%RH (no condensation)
Drop Specification	In the operating temperature range, 6 sides can withstand 1.2m height 30 impacts on concrete floor
Rolling Test Protection Sealing	500×0.5m rolling for 6 sides IP66

Accessories

Standard	Adapter, Data cable, Protective film, Instruction manual

SENTER®

SHANDONG SENTER ELECTRONIC CO., LTD.

www.senter-e.com sales@senter.com.cn